



Castrol Hysol SL 36 XBB

High performance semi-synthetic metalworking fluid

Description

Castrol Hysol™ SL 36 XBB is a high performance semi synthetic metalworking fluid which is free from chlorine, formaldehyde releasing agent and boron. It contains an additive package that may help to enhance machining performance and surface finish, provide excellent product stability and lower overall operating costs.

Castrol Hysol SL 36 XBB is suitable for large central systems and single sump machines.

Application

Hysol SL 36 XBB is especially designed for machining of cast iron and low-medium alloyed steel.

ü ü suggested core application ü possible application, please consult Castrol representative prior to use

	Cast Iron	Low-medium alloyed steel	High alloyed - stainless steel	Aluminium alloys	Magnesium alloys	Yellow metals
Grinding	ü ü	ü ü	ü ü	ü		
Milling, Turning (general machining)	ü ü	ü ü	ü	ü		
Drilling	ü ü	ü ü	ü	ü		
Reaming, Tapping	ü ü	ü		ü		
Broaching	ü ü	ü				

Advantages

- Boron free to meet waste requirements
- Chlorine, formaldehyde releasing agent and nitrite free which may help you to fulfill aspects of legislative requirements and waste treatment requirements that specify that these chemicals are excluded
- Extend fluid life can help reduce maintenance and machine downtime
- Low foam in recommended water conditions (see details below)
- Excellent anti-corrosion properties to protect machine tools and parts
- Good wetting properties can help reduce coolant drag out and help deliver cleaner machine tools and components
- Suitable for a wide range of materials and applications provides opportunity for product consolidation

Typical Characteristics

	Test Method	Unit	Value
<u>Concentrate</u>			
Appearance	Visual		Amber
Mineral oil content	Calculated	Wt%	30
<u>Emulsion</u>			
Appearance	Visual		transluzent
pH (3%)	DIN 51369 ASTM E70-97		9.3
Refractometer Factor			1.2

Subject to usual manufacturing tolerances.

Recommended Concentrations

Grinding 4-6%
General Machining 5-10%

Water range 50-400 ppm CaCO₃

Additional Information

	Boron	Formaldehyde releasing agent	EP-Ester	Amines	Chlorine
Additives			ü	ü	

Storage

To avoid product deterioration always keep the container/drum tightly sealed. Store the product in a cool, dry place away from direct sunlight. Prevent exposure to frost and avoid water ingress. For optimum product stability, it is preferable to store the product indoors between 5°C and 45 °C / 41°F and 113°F.

For more details, please refer the product safety data sheet.

Castrol Hysol SL 36 XBB
17 Nov 2020
Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 352, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW
Orders/Enquiries: 0345 9645111 Technical Enquiries: 0345 082 1719
www.castrol.com/industrial