SAFETY DATA SHEET



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name Castrol Transmax Axle Long Life 75W-90

Product code 469698-DE01
SDS no. 469698
Product type Liquid.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/ Automotive gear lubricant

mixture For specific application advice see appropriate Technical Data Sheet or consult our company

representative.

1.3 Details of the supplier of the safety data sheet

Supplier Castrol Lubricants, Div.BP Europa SE - BP Belgium

Amocolaan 2 2440 Geel BELGIE Tel. 03 2860811

E-mail address MSDSadvice@bp.com

1.4 Emergency telephone number

EMERGENCY Carechem: +44 (0) 1235 239 670 (24/7)

TELEPHONE NUMBER

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Not classified.

See sections 11 and 12 for more detailed information on health effects and symptoms and environmental hazards.

2.2 Label elements

Signal word No signal word.

Hazard statements No known significant effects or critical hazards.

Precautionary statements

PreventionNot applicable.ResponseNot applicable.StorageNot applicable.DisposalNot applicable.

Supplemental label Contains Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide,

elements propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14- tert-alkyl.

May produce an allergic reaction. Safety data sheet available on request.

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Special packaging requirements

Containers to be fitted with child-resistant

Not applicable.

Not applicable.

fastenings

Product nameCastrol Transmax Axle Long Life 75W-90Product code469698-DE01Page: 1/11Version 4Date of issue 23 February 2022FormatBelgiumLanguageENGLISH

Date of previous issue 1 April 2021. (Belgium)

SECTION 2: Hazards identification

Tactile warning of danger Not applicable.

2.3 Other hazards

Results of PBT and vPvB

assessment

Product meets the criteria for PBT or vPvB according to Regulation (EC) No.

Annex XIII.

Product does not meet the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006,

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

1907/2006, Annex XIII
Other hazards which do
not result in classification

Defatting to the skin.

Experimental data on one or more of the components has been used to determine all or part of the hazard classification of this product.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Product definition Mixture

Synthetic base stock. Proprietary performance additives.

Product/ingredient % Regulation (EC) No. Identifiers **Type** 1272/2008 [CLP] name Polysulfides, di-tert-Bu [1] REACH #: 01-2119540515-43 ≤5 Skin Sens. 1B, H317 EC: 273-103-3 Aquatic Chronic 3, H412 CAS: 68937-96-2 [1] Reaction products of 4-methyl-Acute Tox. 4, H302 REACH #: 01-2119493620-38 ≤1.9 2-pentanol and diphosphorus EC: -Eye Dam. 1, H318 pentasulfide, propoxylated, esterified CAS: -Skin Sens. 1B, H317 with diphosphorus pentaoxide, and Aquatic Chronic 2, H411 salted by amines, C12-14- tert-alkyl

See Section 16 for the full text of the H statements declared above.

Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

- [3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII
- [4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

[5] Substance of equivalent concern

[6] Additional disclosure due to company policy

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Eyelids

should be held away from the eyeball to ensure thorough rinsing. Check for and remove any

contact lenses. Get medical attention.

Skin contact Wash skin thoroughly with soap and water or use recognised skin cleanser. Remove

contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before

reuse. Get medical attention if irritation develops.

symptoms may be delayed. The exposed person may need to be kept under medical

surveillance for 48 hours. Get medical attention if symptoms occur.

Ingestion Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if

symptoms occur.

Protection of first-aidersNo action shall be taken involving any personal risk or without suitable training.

4.2 Most important symptoms and effects, both acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

Potential acute health effects

Inhalation Exposure to decomposition products may cause a health hazard. Serious effects may be

delayed following exposure.

Ingestion No known significant effects or critical hazards.

Product nameCastrol Transmax Axle Long Life 75W-90Product code469698-DE01Page: 2/11Version 4Date of issue 23 February 2022FormatBelgiumLanguageENGLISHDate of previous issue1 April 2021.(Belgium)

SECTION 4: First aid measures

Skin contact Defatting to the skin. May cause skin dryness and irritation. Product not classified for

sensitisation. Based on data available for this or related materials.

Eye contact Not classified as an eye irritant. Based on data available for this or related materials.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Inhalation Overexposure to the inhalation of airborne droplets or aerosols may cause irritation of the

respiratory tract.

Ingestion Ingestion of large quantities may cause nausea and diarrhoea.

Skin contact Prolonged or repeated contact can defat the skin and lead to irritation and/or dermatitis.

Eye contact Potential risk of transient stinging or redness if accidental eye contact occurs.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician reatment should in general be symptomatic and directed to relieving any effects. In case of inhalation of decomposition products in a fire, symptoms may be delayed.

The exposed person may need to be kept under medical surveillance for 48 hours.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing

In case of fire, use foam, dry chemical or carbon dioxide extinguisher or spray.

Unsuitable extinguishing

media

media

Do not use water jet. The use of a water jet may cause the fire to spread by splashing the

burning product.

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture In a fire or if heated, a pressure increase will occur and the container may burst.

Hazardous combustion

combustion products may include the following:

products

carbon oxides (CO, CO₂) (carbon monoxide, carbon dioxide)

nitrogen oxides (NO, NO₂ etc.)

5.3 Advice for firefighters

Special precautions for fire-fighters

equipment for fire-fighters

Special protective

No action shall be taken involving any personal risk or without suitable training. Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire.

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for firefighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Floors may be slippery; use care to avoid falling. Put on appropriate personal protective equipment.

For emergency responders

If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-

emergency personnel".

6.2 Environmental precautions

Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

6.3 Methods and material for containment and cleaning up

Small spill Stop leak if without risk. Move containers from spill area. Absorb with an inert material and

place in an appropriate waste disposal container. Dispose of via a licensed waste disposal

Large spill Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water

courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor.

Product name Castrol Transmax Axle Long Life 75W-90 Product code 469698-DE01 Page: 3/11

Language ENGLISH Version 4 Date of issue 23 February 2022 Format Belgium

(Belgium) 1 April 2021. Date of previous issue

SECTION 6: Accidental release measures

6.4 Reference to other sections

See Section 1 for emergency contact information.

See Section 5 for firefighting measures.

See Section 8 for information on appropriate personal protective equipment.

See Section 12 for environmental precautions.

See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Protective measures

Put on appropriate personal protective equipment.

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Wash thoroughly after handling. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional

information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10). Keep away from heat and direct sunlight. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Store and use only in equipment/ containers designed for use with this product. Do not store in unlabelled containers.

Not suitable Prolonged exposure to elevated temperature.

7.3 Specific end use(s)

Recommendations See section 1.2 and Exposure scenarios in annex, if applicable.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

No exposure limit value known.

Whilst specific OELs for certain components may be shown in this section, other components may be present in any mist, vapour or dust produced. Therefore, the specific OELs may not be applicable to the product as a whole and are provided for guidance only.

Recommended monitoring procedures

If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Derived No Effect Level

No DNELs/DMELs available.

Predicted No Effect Concentration

No PNECs available

8.2 Exposure controls

Appropriate engineering controls

Provide exhaust ventilation or other engineering controls to keep the relevant airborne concentrations below their respective occupational exposure limits.

All activities involving chemicals should be assessed for their risks to health, to ensure exposures are adequately controlled. Personal protective equipment should only be considered after other forms of control measures (e.g. engineering controls) have been suitably evaluated. Personal protective equipment should conform to appropriate standards, be suitable for use, be kept in good condition and properly maintained.

Your supplier of personal protective equipment should be consulted for advice on selection and appropriate standards. For further information contact your national organisation for standards. The final choice of protective equipment will depend upon a risk assessment. It is important to ensure that all items of personal protective equipment are compatible.

Individual protection measures

Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location.

Respiratory protection

Product name Castrol Transmax Axle Long Life 75W-90

Product code 469698-DE01

Page: 4/11

Version 4 Date of issue 23 February 2022

Format Belgium

Language ENGLISH

Date of previous issue 1 April 2021.

(Belgium)

SECTION 8: Exposure controls/personal protection

In case of insufficient ventilation, wear suitable respiratory equipment.

The correct choice of respiratory protection depends upon the chemicals being handled, the conditions of work and use, and the condition of the respiratory equipment. Safety procedures should be developed for each intended application. Respiratory protection equipment should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

Eye/face protection
Skin protection
Hand protection

Safety glasses with side shields.

General Information:

Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. The correct choice of protective gloves depends upon the chemicals being handled, and the conditions of work and use. Most gloves provide protection for only a limited time before they must be discarded and replaced (even the best chemically resistant gloves will break down after repeated chemical exposures).

Gloves should be chosen in consultation with the supplier / manufacturer and taking account of a full assessment of the working conditions.

Recommended: Nitrile gloves.

Breakthrough time:

Breakthrough time data are generated by glove manufacturers under laboratory test conditions and represent how long a glove can be expected to provide effective permeation resistance. It is important when following breakthrough time recommendations that actual workplace conditions are taken into account. Always consult with your glove supplier for up-to-date technical information on breakthrough times for the recommended glove type. Our recommendations on the selection of gloves are as follows:

Continuous contact:

Gloves with a minimum breakthrough time of 240 minutes, or >480 minutes if suitable gloves can be obtained.

If suitable gloves are not available to offer that level of protection, gloves with shorter breakthrough times may be acceptable as long as appropriate glove maintenance and replacement regimes are determined and adhered to.

Short-term / splash protection:

Recommended breakthrough times as above.

It is recognised that for short-term, transient exposures, gloves with shorter breakthrough times may commonly be used. Therefore, appropriate maintenance and replacement regimes must be determined and rigorously followed.

Glove Thickness:

For general applications, we recommend gloves with a thickness typically greater than 0.35 mm.

It should be emphasised that glove thickness is not necessarily a good predictor of glove resistance to a specific chemical, as the permeation efficiency of the glove will be dependent on the exact composition of the glove material. Therefore, glove selection should also be based on consideration of the task requirements and knowledge of breakthrough times. Glove thickness may also vary depending on the glove manufacturer, the glove type and the glove model. Therefore, the manufacturers' technical data should always be taken into account to ensure selection of the most appropriate glove for the task.

Note: Depending on the activity being conducted, gloves of varying thickness may be required for specific tasks. For example:

- Thinner gloves (down to 0.1 mm or less) may be required where a high degree of manual dexterity is needed. However, these gloves are only likely to give short duration protection and would normally be just for single use applications, then disposed of.
- Thicker gloves (up to 3 mm or more) may be required where there is a mechanical (as well as a chemical) risk i.e. where there is abrasion or puncture potential.

Product nameCastrol Transmax Axle Long Life 75W-90Product code469698-DE01Page: 5/11Version 4Date of issue 23 February 2022FormatBelgiumLanguageENGLISHDate of previous issue1 April 2021.(Belgium)

SECTION 8: Exposure controls/personal protection

Skin and bodyUse of protective clothing is good industrial practice.

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this

product.

Cotton or polyester/cotton overalls will only provide protection against light superficial contamination that will not soak through to the skin. Overalls should be laundered on a regular basis. When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots

will be required.

Refer to standards: Respiratory protection: EN 529

Gloves: EN 420, EN 374 Eye protection: EN 166 Filtering half-mask: EN 149

Filtering half-mask with valve: EN 405 Half-mask: EN 140 plus filter Full-face mask: EN 136 plus filter

Particulate filters: EN 143
Gas/combined filters: EN 14387

Environmental exposure

controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to

reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance

Physical state
Colour
Amber.

Odour
Not available.
Odour threshold
Not applicable.

Melting point/freezing point
Initial boiling point and boiling
range
Liquid.
Amber.
Not available.
Not available.
Not available.

Pour point

-57 °C

Flash point

Open cup: >205°C (>401°F) [Cleveland]

Evaporation rateNot available.Flammability (solid, gas)Not available.Upper/lower flammability orNot available.

explosive limits

ivol avallable.

Vapour pressure

Not available.

	Vapour Pressure at 20°C		Vapour pressure at 50°C			
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method
pec-1-ene, homopolymer, hydrogenated	0	0	ASTM E 1194-87			
Dec-1-ene, homopolymer, hydrogenated	0	0	ASTM E 1194-87			
diisodecyl azelate	0	0				
Polysulfides, di-tert-Bu	0.12	0.016	OECD 104			

Vapour densityNot available.Relative densityNot available.

Density <1000 kg/m³ (<1 g/cm³) at 15°C

Solubility(ies)
Partition coefficient: n-octanol/

water

insoluble in water.

Not applicable.

Auto-ignition temperature

Product nameCastrol Transmax Axle Long Life 75W-90Product code469698-DE01Page: 6/11Version 4Date of issue 23 February 2022FormatBelgiumLanguageENGLISHDate of previous issue1 April 2021.(Belgium)

SECTION 9: Physical and chemical properties

Ingredient name	°C	0 F	Mothod
Ingredient name		· F	Method
pec-1-ene, homopolymer, hydrogenated	343 to 369	649.4 to 696.2	ASTM D 2159
Dec-1-ene, homopolymer, hydrogenated	343 to 369	649.4 to 696.2	ASTM D 2159

Decomposition temperature

Viscosity

Not available.

Kinematic: 101 mm²/s (101 cSt) at 40°C

Kinematic: 14.8 to 15.8 mm²/s (14.8 to 15.8 cSt) at 100°C

Explosive properties Not available.

Oxidising properties Not available.

Particle characteristics

Median particle size

Not applicable.

9.2 Other informationNo additional information.

SECTION 10: Stability and reactivity

10.1 Reactivity

No specific test data available for this product. Refer to Conditions to avoid and Incompatible

materials for additional information.

10.2 Chemical stability The product is stable.

10.3 Possibility of hazardous reactions

Under normal conditions of storage and use, hazardous reactions will not occur. Under normal conditions of storage and use, hazardous polymerisation will not occur.

10.4 Conditions to avoid Avoid all possible sources of ignition (spark or flame).

10.5 Incompatible materials Reactive or incompatible with the following materials: oxidising materials.

10.6 Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
Zastrol Transmax Axle Long Life 75W-90 Amines, C12-14-alkyl, reaction products with hexanol, phosphorus oxide (P2O5), phosphorus sulphide (P2S5) and propylene oxide	31146.8	N/A	N/A	N/A	N/A
	500	N/A	N/A	N/A	N/A

Information on likely routes of exposure

Routes of entry anticipated: Dermal, Inhalation.

Potential acute health effects

Inhalation Exposure to decomposition products may cause a health hazard. Serious effects may be

delayed following exposure.

Ingestion No known significant effects or critical hazards.

Skin contact Defatting to the skin. May cause skin dryness and irritation. Product not classified for

sensitisation. Based on data available for this or related materials.

Eye contact Not classified as an eye irritant. Based on data available for this or related materials.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation May be harmful by inhalation if exposure to vapour, mists or fumes resulting from thermal

decomposition products occurs.

Ingestion No specific data.

Skin contact Adverse symptoms may include the following:

irritation dryness cracking

Product nameCastrol Transmax Axle Long Life 75W-90Product code469698-DE01Page: 7/11Version 4Date of issue 23 February 2022FormatBelgiumLanguageENGLISH

Date of previous issue 1 April 2021. (Belgium)

SECTION 11: Toxicological information

Eye contact No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Inhalation Overexposure to the inhalation of airborne droplets or aerosols may cause irritation of the

respiratory tract.

Ingestion Ingestion of large quantities may cause nausea and diarrhoea.

Skin contact Prolonged or repeated contact can defat the skin and lead to irritation and/or dermatitis.

Eye contact Potential risk of transient stinging or redness if accidental eye contact occurs.

Potential chronic health effects

General

No known significant effects or critical hazards.

Carcinogenicity

No known significant effects or critical hazards.

Mutagenicity

No known significant effects or critical hazards.

Developmental effects

No known significant effects or critical hazards.

Fertility effects

No known significant effects or critical hazards.

No known significant effects or critical hazards.

SECTION 12: Ecological information

12.1 Toxicity

Environmental hazards Not classified as dangerous

12.2 Persistence and degradability

Not expected to be rapidly degradable.

12.3 Bioaccumulative potential

This product is not expected to bioaccumulate through food chains in the environment.

12.4 Mobility in soil

Soil/water partition

coefficient (Koc)

Not available.

Mobility Spillages may penetrate the soil causing ground water contamination.

12.5 Results of PBT and vPvB assessment

Product does not meet the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII.

12.6 Other adverse effects

Other ecological information Spills may form a film on water surfaces causing physical damage to organisms. Oxygen

transfer could also be impaired.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Methods of disposal Where possible, arrange for product to be recycled. Dispose of via an authorised person/

licensed waste disposal contractor in accordance with local regulations.

Hazardous waste Yes.

<u>European waste catalogue (EWC)</u>

Waste code	Waste designation
13 02 06*	synthetic engine, gear and lubricating oils

However, deviation from the intended use and/or the presence of any potential contaminants may require an alternative waste disposal code to be assigned by the end user.

Packaging

Methods of disposal Where possible, arrange for product to be recycled. Dispose of via an authorised person/

licensed waste disposal contractor in accordance with local regulations.

Special precautionsThis material and its container must be disposed of in a safe way. Empty containers or liners

may retain some product residues. Avoid dispersal of spilt material and runoff and contact with

soil, waterways, drains and sewers.

References Commission 2014/955/EU

Directive 2008/98/EC

Product nameCastrol Transmax Axle Long Life 75W-90Product code469698-DE01Page: 8/11Version 4Date of issue 23 February 2022FormatBelgiumLanguageENGLISHDate of previous issue1 April 2021.(Belgium)

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.
Additional information	-	-	-	-

14.6 Special precautions for user

Not available.

14.7 Transport in bulk according to IMO instruments

Not available.

Not applicable.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Other regulations

REACH Status The company, as identified in Section 1, sells this product in the EU in compliance with the

current requirements of REACH.

United States inventory

(TSCA 8b)

All components are active or exempted.

Australia inventory (AIIC) All components are listed or exempted. **Canada inventory** All components are listed or exempted. China inventory (IECSC) All components are listed or exempted. Japan inventory (CSCL) All components are listed or exempted. Korea inventory (KECI) All components are listed or exempted. **Philippines inventory** At least one component is not listed.

(PICCS)

All components are listed or exempted.

Taiwan Chemical Substances Inventory

(TCSI)

Ozone depleting substances (1005/2009/EU)

Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

Product name Castrol Transmax Axle Long Life 75W-90 Product code 469698-DE01 Page: 9/11 Version 4 Date of issue 23 February 2022 Format Belgium Language ENGLISH (Belgium) 1 April 2021. Date of previous issue

SECTION 15: Regulatory information

Not listed.

Persistent Organic Pollutants

Not listed.

EU - Water framework directive - Priority substances

None of the components are listed.

Seveso Directive

This product is not controlled under the Seveso Directive.

15.2 Chemical safety assessment

A Chemical Safety Assessment has been carried out for one or more of the substances within this mixture. A Chemical Safety Assessment has not been carried out for the mixture itself.

SECTION 16: Other information

Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by

ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

CAS = Chemical Abstracts Service

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

CSA = Chemical Safety Assessment

CSR = Chemical Safety Report

DMEL = Derived Minimal Effect Level

DNEL = Derived No Effect Level

EINECS = European Inventory of Existing Commercial chemical Substances

ES = Exposure Scenario

EUH statement = CLP-specific Hazard statement

EWC = European Waste Catalogue

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as

modified by the Protocol of 1978. ("Marpol" = marine pollution)

OECD = Organisation for Economic Co-operation and Development

PBT = Persistent, Bioaccumulative and Toxic

PNEC = Predicted No Effect Concentration

REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006]

RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail

RRN = REACH Registration Number

SADT = Self-Accelerating Decomposition Temperature

SVHC = Substances of Very High Concern

STOT-RE = Specific Target Organ Toxicity - Repeated Exposure

STOT-SE = Specific Target Organ Toxicity - Single Exposure

TWA = Time weighted average

UN = United Nations

UVCB = Complex hydrocarbon substance

VOC = Volatile Organic Compound

vPvB = Very Persistent and Very Bioaccumulative

Varies = may contain one or more of the following 64741-88-4 / RRN 01-2119488706-23,

64741-89-5 / RRN 01-2119487067-30, 64741-95-3 / RRN 01-2119487081-40, 64741-96-4/ RRN

01-2119483621-38, 64742-01-4 / RRN 01-2119488707-21, 64742-44-5 / RRN

01-2119985177-24, 64742-45-6, 64742-52-5 / RRN 01-2119467170-45, 64742-53-6 / RRN

01-2119480375-34, 64742-54-7 / RRN 01-2119484627-25, 64742-55-8 / RRN

01-2119487077-29, 64742-56-9 / RRN 01-2119480132-48, 64742-57-0 / RRN

01-2119489287-22, 64742-58-1, 64742-62-7 / RRN 01-2119480472-38, 64742-63-8,

64742-65-0 / RRN 01-2119471299-27, 64742-70-7 / RRN 01-2119487080-42, 72623-85-9 /

RRN 01-2119555262-43, 72623-86-0 / RRN 01-2119474878-16, 72623-87-1 / RRN

01-2119474889-13

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Not classified.	

Product nameCastrol Transmax Axle Long Life 75W-90Product code469698-DE01Page: 10/11Version 4Date of issue 23 February 2022FormatBelgiumLanguageENGLISHDate of previous issue1 April 2021.(Belgium)

SECTION 16: Other information

Full text of abbreviated H Harmful if swallowed.

statementsH317May cause an allergic skin reaction.H318Causes serious eye damage.

H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.

[CLP/GHS] Aquatic Chronic 2 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3 Eye Dam. 1 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1

Skin Sens. 1B SKIN SENSITISATION - Category 1B

SKIT SETS. TB SKIN SENSITISATION - Category

History

Date of issue/ Date of 23/02/2022.

revision

Date of previous issue 01/04/2021.

Prepared by Product Stewardship

Indicates information that has changed from previously issued version.

Notice to reader

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from BP Group.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken. You can contact the BP Group to ensure that this document is the most current available. Alteration of this document is strictly prohibited.

Product nameCastrol Transmax Axle Long Life 75W-90Product code469698-DE01Page: 11/11Version 4Date of issue 23 February 2022FormatBelgiumLanguageENGLISHDate of previous issue1 April 2021.(Belgium)